



# FLEX

MULTIFLEX GRP ROOFING SYSTEM



- ✓ Suitable for New Roofs, Overlays, Balconies & Walkways
- ✓ Easy to Use Topcoat & Primer
- ✓ Fire Rated to EXT. F.A.A.
- ✓ 20 Year Material Guarantee\*
- ✓ Cold Applied
- ✓ Seamless Design
- ✓ Cures at Low Ambient Temperatures (5°C minimum)
- ✓ Flexible
- ✓ (\*Guarantee Terms & Conditions Apply)

**Tricel Composites (GB)**  
Unit A Fox Way, Atkinson Street,  
Leeds LS10 1PS, UK  
**Tel:** +44 113 270 3133

**Tricel Composites (NI)**  
Milltown Industrial Estate, Greenan Rd,  
Warrenpoint, Newry BT34 3FN, UK  
**Tel:** +44 28 4175 3738

[www.triroof.co.uk](http://www.triroof.co.uk)

TOUCH  
DRY  
IN TWO HOURS

SOLVENT  
FREE

CAN BE LAID ON  
DAMP  
SURFACES

USE STRAIGHT  
OUT OF  
THE TIN

NO  
JOINS

GREAT FOR  
COMPLEX  
SHAPED  
AREAS

SELF-  
LEVELLING  
FOR A GREAT FINISH

TriRoof

# HPX

HYBRID POLYMER ROOFING SYSTEM

GUARANTEE  
10 YEAR  
SINGLE LAYER\*

GUARANTEE  
20 YEAR  
DOUBLE LAYER\*



## Product Description

Premium roofing system that repairs, restores, waterproofs and protects.

- Adheres to most substrates incl. asphalt, felt, rubber, concrete, most metals, roofs and flooring\*\*
- Ideal for roofs, balconies, terraces and wet rooms
- Exceptionally flexible (up to 300 times its normal size)

## Other Uses

- Wet rooms
- Wet areas (under-tile) in bathrooms, kitchens, balconies, auxiliary rooms, etc.
- Available in light and dark grey

## 20 & 10 YEAR GUARANTEE\*

- Tack-free time: 2-4 hrs
- Full cure time: 8-16 hrs
- Fibre free formula

## Why use the TriRoof HPX System?

- Can be applied to damp surfaces
- One coat application, easy to use
- Solvent-free, non-flammable
- Suitable for working temperatures of +5°C to +35°C
- Temperature resistant (once cured) -20°C to +80°C
- Breathable until cured, allowing moisture to evaporate
- Contains stain reducing properties

### \*20 Year Guarantee

Repair any leaks with HPX and TriRoof CSM 450gm Bandage consolidated. Then apply 1 Layer of HPX (1.6 – 1.8kg sqm depending on substrate) with Triroof 225g CSM consolidated followed up with a 1.3 kg sqm final coat after first layer has dried.

### \*10 Year Guarantee

Repair any leaks with HPX and TriRoof CSM 450gm Bandage consolidated then 1 layer of HPX (1.6kg sqm – 1.8kg sqm depending on substrate).

\*\*Adheres to most surfaces. Testing is advised prior to install. All containments must be removed prior to install.

### Tricel Composites (GB)

Unit A Fox Way, Atkinson Street,  
Leeds LS10 1PS, UK  
Tel: +44 113 270 3133

### Tricel Composites (NI)

Milltown Industrial Estate, Greenan Rd,  
Warrenpoint, Newry BT34 3FN, UK  
Tel: +44 28 4175 3738

[www.triroof.co.uk](http://www.triroof.co.uk)