



MATERIAL SAFETY DATA SHEET

TRIROOF MULTIFLEX PRIMER

Product Name:	TriRoof MultiFlex Primer 1339198 Rev.2
Revision Date:	11-Oct-2023 According to Regulation (EC) No. 1907/2006

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name: TriRoof MultiFlex Primer

1.2. Product relevant identified uses of the substance or mixture and uses advised against

Used in a variety of polyester resin system within the fiberglass moulding industry

1.3. Details of the supplier of the safety data sheet

Tricel Composites (GB) Limited

Unit A, Foxway,
Off Atkinson Street,
Leeds, West Yorkshire,
LS10 1PS.
Tel: +44 (0)113 270 3133

Tricel Composites (NI) Limited

Unit 4, Milltown Ind. Estate, Greenan
Road. Warrenpoint, Newry
Co. Down,
BT34 3FN.
Tel: +44 (0)284 175 3738

1.4. Emergency Telephone Number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Telephone Number: +353 (0)1 809 2166

Leeds:	Newry:
Tel: +44 (0)113 270 3133	Tel: +44 (0)284 175 3738

1.4.1. Poison Information Centre Telephone Number

European emergency phone number: 112

UK: National Poisons Emergency Number : 0344 892 0111

Ireland: National Poisons Information Centre (NPIC) Telephone Healthcare Professionals : +353 (01) 809 2566. (24 hour service) Telephone Members of Public: +353 (01) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week)

2. Hazards Identification

2.1. Classification of the substance or mixture

CLP: Lact., Skin Sens. 1, Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2, Repr. 2, STOT SE 3, STOT RE 1, Aquatic Chronic 3.

2.2. Label elements

Hazard Pictograms:



GHS02



GHS08



GHS07

Signal Word: Danger

2.2.1. Hazard Statements

H226 – Flammable liquid and vapour.

H361 – Suspected of damaging fertility or the unborn child.

H362 – May cause harm to breast-fed children.

H335 – May cause respiratory irritation.

H372 – Causes damage to organs through prolonged or repeated exposure.

H315 – Causes skin irritation.

H319 – Causes serious eye irritation.

H317 – May cause an allergic skin reaction.

H412 – Harmful to aquatic life with long lasting effects.

EUH211 – Warning! Hazardous respirable droplets may be formed when sprayed.

Do not breathe spray or mist.

2.2.2. Precautionary Statements

P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P403+P235 – Store in a well-ventilated place. Keep cool.

P260 – Do not breathe dust/fume/gas/mist/vapours/spray.

P403+P233 – Store in a well-ventilated place. Keep container tightly closed.

P261 – Avoid breathing dust/fume/gas/mist/vapours/spray.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 – IF exposed or concerned: Get medical advice/attention.

P281 – Use personal protective equipment as required.

P370+P378 – In case of fire: use foam, carbon dioxide or dry agent to extinguish.

P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P263 – Avoid contact during pregnancy and while nursing.

P201 – Obtain special instructions before use.

P273 – Avoid release to the environment.

P501 – Dispose of contents/container to an authorised waste collection point

P312 – Call a POISON CENTRE or doctor if you feel unwell.

P233 – Keep container tightly closed.

P314 – Get medical advice/attention if you feel unwell.

P264 – Wash hands thoroughly after handling.

P337+P313 – If eye irritation persists: Get medical advice/attention.

P333+P313 – If skin irritation or rash occurs: Get medical advice/attention.

P363 – Wash contaminated clothing before reuse.

P271 – Use only outdoors or in a well-ventilated area.

P302+P352 – IF ON SKIN: Wash with plenty of soap and water.

P270 – Do not eat, drink or smoke when using this product.

P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P243 – Take action to prevent static discharges.

P332+P313 – If skin irritation occurs: Get medical advice/attention.

P240 – Ground and bond container and receiving equipment.

P405 – Store locked up.

P241 – Use explosion-proof equipment.

P272 – Contaminated work clothing should not be allowed out of the workplace.

P242 – Use non-sparking tools.

P362+P364 – Take off contaminated clothing and wash it before reuse.

P202 – Do not handle until all safety precautions have been read and understood.

2.3. Other Hazards

Contains: Methyl Methacrylate, styrene

3. Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

	CAS Number	EC Number	REACH Registration Number	Concentrat ion	Categories	Symbols
styrene	100-42-5	202-851-5	01-2119457861-32-xxxx	< 50%	Flam. Liq. 3 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2 Repr. 2 STOT SE 3 STOT RE 1 Asp. Tox. 1 Aquatic Chronic 3	GHS02 GHS07 GHS08
Aluminium Hydroxide	21645-51-2	244-492-7	01-2119529246-39-XXXX	< 10%		
METHYL METHACRYLATE	80-62-6	201-297-1	01-2119452498-28-XXXX	< 10%	Flam. Liq. 2 Skin Irrit. 2 Skin Sens. 1 STOT SE 3	GHS03 GHS07
Titanium dioxide	13463-67-7	236-675-5	01-2119489379-17-XXXX	< 5%		
Distillates (petroleum), hydrotreated light paraffinic; Baseoil -unspecified	64742-55-8	265-158-7	01-2119487077-29-XXXX	< 5%	Asp. Tox. 1	GHS08
Silicon dioxide	112945-52-5	231-545-4	01-2119379499-16-XXXX	< 5%		

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	265-199-0	01-2119486773-24-XXXX	< 1%	Flam. Liq. 3 STOT SE 3 Asp. Tox. 1 Aquatic Chronic 2 Aquatic Chronic 1	GHS02 GHS09
COBALT NEODECANOATE	27253-31-2	248-373-0	01-2119970733-31-0006	< 1%	Acute Tox. 4 Skin Sens. 1 STOT RE 1 Aquatic Chronic 3	GHS08
POTASSIUM 2-ETHYLHEXANOATE	3164-85-0	221-625-7	01-2119980714-29-0013	< 1%	Skin Irrit. 2 Eye Dam. 1 Repr. 2	
2-methoxy- 1-methylethyl acetate	108-65-6	203-603-9	01-2119475791-29-XXXX	< 1%	Flam. Liq. 3 STOT SE 3	
Ethanol	64-17-5	200-578-6	01-2119457610-43-XXXX	< 1%	Flam. Liq. 2 Eye Irrit. 2	GHS02 GHS07 GHS08
DE-AROMATISED KEROSENE	64742-48-9	918-481-9	01-2119457273-39-XXXX	< 1%	Asp. Tox. 1	
Methoxy Propoxy Propanol	34590-94-8	252-104-2	01-2119450011-60-xxxx	< 1%		
HYDROQUINONE	123-31-9	204-617-8	01-2119524016-51-xxxx	< 1%	Acute Tox. 4 Eye Dam. 1 Skin Sens. 1 Muta. 2 Carc. 2 Aquatic Acute 1 Aquatic Chronic 1	GHS05 GHS07 GHS08 GHS09
2-ETHYLHEXANOIC ACID	149-57-5	205-743-6	01-2119488942-23	< 1%	Repr. 2	
Propylidyntrimethanol	77-99-6	201-074-9	01-2119486799-10-XXXX	< 1%	Repr. 2	
Methanol	67-56-1	200-659-6	01-2119433307-44-XXXX	< 1%	Flam. Liq. 2 Acute Tox. 3 STOT SE 1	GHS02 GHS06 GHS08
2,6-di-tert-butyl-p-cresol	128-37-0	204-881-4	01-2119565113-46-XXXX	< 1%	Aquatic Acute 1 Aquatic Chronic 1	GHS09

octamethylcyclotetrasiloxane	556-67-2	209-136-7	01-2119529238-36-XXXX	< 1%	Flam. Liq. 3 Repr. 2 Aquatic Chronic 4	GHS02 GHS08 GHS09
decamethylcyclopentasiloxane	541-02-6	208-764-9	01-2119511367-43-XXXX	< 1%		
dodecamethylcyclohexasiloxane	540-97-6	208-762-8	01-2119517435-42-XXXX	< 1%		

	H Statements	Mfactor, acute	Mfactor, chronic	Mfactor
styrene	H226 H304 H315 H319 H332 H335 H361d H372			
Aluminium Hydroxide				
METHYL METHACRYLATE	H225 H315 H317 H335			
Titanium dioxide				
Distillates (petroleum), hydrotreated light paraffinic; Baseoil -unspecified	H304			
Silicon dioxide				
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	H226 H304 H335 H336 H411			
COBALT NEODECANOATE	H302 H317 H372 H412			
POTASSIUM 2-ETHYLHEXANOATE	H315 H318 H361			
2-methoxy- 1-methylethyl acetate	H226 H336			

Ethanol	H225 H319			
DE- AROMATISED KEROSENE	H304			
Methoxy Propoxy Propanol				
HYDROQUINONE	H312 H317 H318 H341 H351 H410 H400	10	1	10;1
2-ETHYLHEXANOIC ACID	H361d			
Propylidynetrimethanol				
Methanol	H225 H331 H301 H311 H370			
2,6-di-tert-butyl-p-cresol	H410 H400			
octamethylcyclotetrasiloxane	H226 H361f H413			
decamethylcyclopentasiloxane				
dodecamethylcyclohexasiloxane				
	H412			

4. First Aid Measures

4.1. Description of First Aid Measures

4.1.1. Contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

4.1.2. Contact with skin

If skin irritation occurs: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTRE or doctor if you feel unwell.

4.1.3. Ingestion

IF exposed or concerned: Get medical advice/attention. Call a POISON CENTRE or doctor if you feel unwell.

4.1.4. Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

5. Firefighting Measures

5.1. Extinguishing media

- In case of fire: use foam, carbon dioxide or dry agent to extinguish.

5.2. Special Hazards arising from substance or mixture

- Flammable and Toxic
- Vapours may ignite

5.3. Advice for Firefighters

- Wear Breathing Apparatus

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

- Wear protective clothing as per section 8

- Vapours may ignite

6.2. Environmental Precautions

- Do not allow to enter public sewers and watercourses
- Do not empty into drains
- Stop leak if safe to do so.
- Use appropriate containment to avoid environmental contamination

6.3. Methods and Material for Containment and Cleaning Up

- Absorb spillage in inert material and shovel up
- Place in sealable container
- Ventilate area
- Wash thoroughly after dealing with spillage

6.4. Reference to other sections

- See section 8

7. Handling and Storage

7.1. Precautions for safe handling

- Avoid contact with organic peroxides
- Call a POISON CENTRE or doctor if you feel unwell.
- Get medical advice/attention if you feel unwell.
- Wash contaminated clothing before reuse.
- Dispose of contents/container to an authorised waste collection point

7.2. Conditions for safe storage, including any incompatibilities

- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Store locked up.

7.3. Specific end use(s)

8. Exposure Controls/Personal Protection

8.1. Exposure Controls

Substances

	DNEL (Industry; dermal, long term systemic effects)	DNEL (Industry; inhalational, long term systemic effects)	DNEL (Industry; inhalational, short term local effects)	DNEL (Industry; inhalational, short term systemic effects)	DNEL (Consumer; dermal, long term systemic effects)	DNEL (Consumer; inhalational, long term systemic effects)
styrene	406 mg/kg/day	85 mg/m ³	306 mg/m ³	289 mg/m ³	343 mg/kg/day	10.2 mg/m ³
Aluminium Hydroxide						
METHYL METHACRYLATE	13.67 mg/kg/day	208 mg/m ³			8.2 mg/kg/day	74.3 mg/m ³
Titanium dioxide						
Distillates (petroleum), hydrotreated light paraffinic; Baseoil -unspecified	1.0 mg/kg	2.7 mg/m ³				
Silicon dioxide						
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	25 mg/kg	150 mg/m ³			11 mg/kg	32 mg/m ³
COBALT NEODECANOATE						
2-methoxy- 1-methylethyl acetate	153.5 mg/kg	275 mg/m ³			54.8 mg/kg	33 mg/m ³

Ethanol	343 mg/kg	950 mg/m³	1900 mg/m³		206 mg/kg	114 mg/m³
DE-AROMATISED KEROSENE						
Methoxy Propoxy Propanol						
HYDROQUINONE	3.33 mg/kg/day	2.1 mg/m³			1.66 mg/kg/day	1.05 mg/m³
Propylidynetrimethanol	0.94 mg/kg	3.3 mg/m³			0.34 mg/kg	0.58 mg/m³
2,6-di-tert-butyl-p-cresol						
octamethylcyclotetrasiloxane					3.7 mg/kg	13 mg/m³

Substances

	DNEL (Consumer; inhalational, short term systemic effects)	DNEL (Consumer; oral, long term systemic effects)	DNEL (Consumer; inhalational, short term local effects)	WEL (long term)	WEL (short term)	WEL (inhalable dust)
styrene	174.25 mg/m³	2.1 mg/kg/day	182.75 mg/m³	1080 mg/m³ (8-hour TWA)	430 mg/m³	
Aluminium Hydroxide						10 mg/m³
METHYL METHACRYLATE						
Titanium dioxide		700 mg/kg bw/day				10 mg/m³ (8 hour TWA)
Distillates (petroleum), hydrotreated light paraffinic; Baseoil -unspecified						
Silicon dioxide						6.0 mg/m³
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified		11 mg/kg				
COBALT NEODECANOATE		0.065 mg/kg bw/day				
2-methoxy- 1-methylethyl acetate		1.67 mg/kg		50 ppm 274 mg/m³ (8-hour TWA)	100 ppm 548 mg/m³	
Ethanol		87 mg/kg	950 mg/m³	1000 ppm 1920 mg/m³ (8-hour TWA)		
DE-AROMATISED KEROSENE				1000 mg/m³ (8-hour TWA)		
Methoxy Propoxy Propanol				50 ppm 308 mg/m³		

HYDROQUINONE		0.6 mg/kg/day		0.5 mg/m ³ (8-hour TWA)		
Propylidynetrimethanol		0.34 mg/kg				
2,6-di-tert-butyl-p-cresol				10 mg/m ³ (8-hour TWA)		
octamethylcyclotetrasiloxane	13 mg/m ³		13 mg/m ³			

Substances

	WEL (respirable dust)	DNEL (Consume r; dermal, long term local effects)	DNEL (Consume r; dermal, short term local effects)	DNEL (Consume r; inhalation al, long term local effects)	DNEL (Industry; dermal, long term local effects)	DNEL (Industry; dermal, short term local effects)
styrene						
Aluminium Hydroxide	4 mg/m ³					
METHYL METHACRYLATE		1.5 mg/cm ²	1.5 mg/cm ²	105 mg/m ³	1.5 mg/cm ²	1.5 mg/cm ²
Titanium dioxide	4 mg/m ³ (8 hour TWA)					
Distillates (petroleum), hydrotreated light paraffinic; Baseoil -unspecified						
Silicon dioxide	2.4 mg/m ³					
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified						
COBALT NEODECANOATE				0.043 mg/m ³		
2-methoxy- 1-methylethyl acetate						
Ethanol						

DE-AROMATISED KEROSENE						
Methoxy Propoxy Propanol						
HYDROQUINONE						
Propylidynetrimethanol						
2,6-di-tert-butyl-p-cresol						
octamethylcyclotetrasiloxane				13 mg/m ³		

Substances

	DNEL (Industry; inhalation al, long term local effects)	DNEL (Industry)	DNEL (dermal)	DNEL (Consumer; dermal, short term systemic effects)
styrene				
Aluminium Hydroxide				
METHYL METHACRYLATE	208 mg/m ³			
Titanium dioxide	10 mg/m ³			
Distillates (petroleum), hydrotreated light paraffinic; Baseoil -unspecified				
Silicon dioxide	4 mg/m ³			
Solvent naphtha (petroleum), light arom.;; Low boiling point naphtha -unspecified				
COBALT NEODECANOATE	0.273 mg/m ³			
2-methoxy-				

1-methylethyl acetate				
Ethanol				
DE-AROMATISED KEROSENE				
Methoxy Propoxy Propanol				
HYDROQUINONE				
Propylidynetrimethanol				
2,6-di-tert-butyl-p-cresol		Inhalation 3.5 mg/kg	Industry 0.5 mg/kg	
octamethylcyclotetrasiloxane				3.7 mg/kg

8.2. Exposure controls

Hand protection: Use appropriate protective gloves (EN 374, EN 420).

Material: rubber, PVC, polyvinyl alcohol, or butyl rubber.



Boots



Gloves



Goggles

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Odour: Perceptible odour

Flammability: Flammable

Solubility in water: Immiscible with water

Flashpoint: 28°C

9.2. Other Information

10. Stability and Reactivity

10.1. Reactivity

- This article is considered stable under normal conditions

10.2. Chemical stability

- This article is considered stable under normal conditions

10.3. Possibility of hazardous reactions

- Vapours may ignite

10.4. Conditions to avoid

- Keep away from heat
- Keep away from naked flames, incandescent or hot surfaces
- Keep away from static electricity
- Keep away from strong oxidizing substances

10.5. Incompatible materials

- Incompatible with organic peroxides

10.6. Hazardous decomposition Products

- May polymerise on exposure to heat and air
- Decomposition products may include toxic fumes

11. Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Acute toxicity

Estimated LD₅₀ (oral) (ATE) : >2000 mg/kg
 Estimated LD₅₀ (dermal) (ATE) : >4000 mg/kg
 Estimated LD₅₀ (inhalational) (ATE) : 27.19407 mg/l/4hr (gas/vapour)

Substances

	LC ₅₀ (inhalation, rat)	LD ₅₀ (oral, rat)	LD ₅₀ (skin, rat)	LD ₅₀ (dermal, rabbit)	LC ₅₀ (inhalation)
styrene	11.8 mg/l/4h	5000 mg/kg	2000 mg/kg		
Aluminium Hydroxide	2.3 mg/l	2000 mg/kg			
Titanium dioxide	6.82 mg/l	5000 mg/kg			
Silicon dioxide		5000 mg/kg		2000 mg/kg	
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified				3.160 mg/kg	
2-methoxy- 1-methylethyl acetate		5000 mg/kg			
Ethanol		2000 mg/kg		2000 mg/kg	20 mg/l
Propylidynetrimethanol		14700 mg/kg			
2,6-di-tert-butyl-p-cresol		2.930 mg/kg	2.000 mg/kg		
octamethylcyclotetrasiloxane	36 mg/l				

11.2. Information on Other Hazards

12. Ecological Information

12.1. Toxicity

Substances

	EC ₅₀ (daphnia)	LC ₅₀ (fish)	PNEC (Fresh water)	PNEC (intermittent)	PNEC (Marine water)	PNEC (Sediment; fresh water)
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	3.2 mg/l (48 hr)					
2,6-di-tert-butyl-p-cresol		199 mg/l (96 hr)	0.000199 mg/l	0.00199 mg/l	0.00002 mg/l	0.0996 mg/kg
2-methoxy- 1-methylethyl acetate		100 mg/l (96 hr)	0.635 mg/l	6.35 mg/l	0.0635 mg/l	3.29 mg/kg
octamethylcyclotetrasiloxane			0.44 mg/l		0.044 mg/l	0.128 mg/kg
Methoxy Propoxy Propanol	Unknown mg/l (48 hr)	Unknown mg/l (96 hr)				
DE-AROMATISED KEROSENE	Unknown mg/l (48 hr)	Unknown mg/l (96 hr)				
styrene	4.7 mg/l (48 hr)	4.02 mg/l (96 hr)	0.028 mg/l	0.04 mg/l	0.014 mg/l	0.614 mg/kg
COBALT NEODECANOATE	Unknown mg/l (48 hr)	Unknown mg/l (96 hr)	0.003 mg/l		0.002 mg/l	9.5 mg/kg
Silicon dioxide	500 mg/l (48 hr)	10000 mg/l (96 hr)				
Titanium dioxide		10000 mg/l (96 hr)	0.184 mg/l	0.193 mg/l	0.0184 mg/l	1000 mg/kg
Propylidynetrimethanol	13000 mg/l (48 hr)	1000 mg/l (96 hr)				
METHYL METHACRYLATE	69 mg/l (48 hr)	130 mg/l (96 hr)				
HYDROQUINONE			0.00057 mg/l		0.000057 mg/l	0.0049 mg/kg
Ethanol			0.96 mg/l		0.79 mg/l	3.6 mg/kg
Methanol	100 mg/l (48 hr)	100 mg/l (96 hr)				

Substances

	PNEC (Sediment; marine water)	PNEC (Soil)	PNEC (STP)	IC ₅₀ (algae)
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified				

2,6-di-tert-butyl-p-cresol	0,0996 mg/kg	0,04769 mg/l		
2-methoxy- 1-methylethyl acetate	0.329 mg/kg	0.29 mg/kg	100 mg/l	
octamethylcyclotetrasiloxane		0.16 mg/kg	100 mg/kg	
Methoxy Propoxy Propanol				Unknown mg/l (72 hr)
DE-AROMATISED KEROSENE				Unknown mg/l (72 hr)
styrene	.307 mg/kg	0.2 mg/kg	5 mg/l	Unknown mg/l (72 hr)
COBALT NEODECANOATE	9.5 mg/kg	10.9 mg/kg	0.37 mg/l	Unknown mg/l (72 hr)
Silicon dioxide				Unknown mg/l (72 hr)
Titanium dioxide	100 mg/kg	100 mg/kg	100 mg/l	
Propylidynetrimethanol				1000 mg/l (72 hr)
METHYL METHACRYLATE				
HYDROQUINONE	0.00049 mg/kg	0.000129 mg/kg	0.71 mg/l	
Ethanol		0.63 mg/kg		
Methanol				

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

- Immiscible in water

12.5. Results of PBT and vPvB

12.6. Endocrine disrupting properties

12.7. Other Adverse Effects

- Toxic to sewage works organisms
- Dispose of contents/container to an authorised waste collection point

13. Disposal Considerations

13.1. Waste Treatment Methods

- Dispose of contents/container to an authorised waste collection point.

14. Transport Information



Flammable Liquid

14.1. UN number or ID number

- UN No.: 1866

14.2. UN proper shipping name

- Proper Shipping Name: RESIN SOLUTION

14.3. Transport hazard class(es)

- Hazard Class: 3

14.4. Packing group

- Packing Group: III

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

15. Regulatory Information

15.1. Safety, Health And Environmental Regulations / Legislation Specific For The Substance Or Mixture

- The ADR Regulations apply in the UK
- The CLP Regulations apply in the UK
- The COSHH Regulations apply in the UK
- The Health and Safety at Work Act applies in the UK
- The Hazardous Waste (England and Wales) Regulations 2005 apply in the UK
- (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 & UK REACH Regulation

15.2. Chemical Safety Assessment

- A REACH chemical safety assessment has not been carried out

16. Other Information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- H304: May be fatal if swallowed and enters airways. H361d: Suspected of damaging the unborn child. GHS03: flame over circle. GHS07: exclamation mark.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may



MATERIAL SAFETY DATA SHEET

not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet